



ASR 80D10  
- Side View -

ASR 80D10  
- Front View -

ASR 80D10  
- Isometric View -

- Notes:
1. Standard heights for Advanced Spring Rater columns shown, custom lengths available
  2. Max Actuator Force: 8000 lbf (3630 Kgf)
  3. Isolation feet removable for permanent installation
  4. Available with safety cage



ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD
PARTS LIST				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		
DECIMALS .X +/- .050		APPROVALS		
ANGLES .XX +/- .010		DRAWN MAF		
.XXX +/- .003		DATE 5-1-07		
MATERIAL --		CHECKED		
FINISH --		RESP ENG		
NEXT ASSY		MFG ENG		
USED ON		QUAL ENG		
APPLICATION		DO NOT SCALE DRAWING		
SIZE A		DWG. NO. --		REV. X
SCALE		CAD FILE:		SHEET 1 OF 1

ROEHRIG ENGINEERING, INC.  
  
Advanced Spring Rater  
Model # ASR 80D10